



Support Note

Support Note: 05-01-042601-Win9598NetInstall

Windows 95/98 Dial-Up Networking Installation

PLEASE NOTE: Before you begin, make sure you have your Windows 95/98 CD-ROM or diskettes available and ready for installation.

1. Double-click **My Computer** on your desktop.
2. Double-click the **Control Panel** icon.
3. Double-click the **Add/Remove Programs** icon.
4. Click the **Windows Setup** tab.
5. Click the **Communications** component.
6. Click the **Details...** button.
7. Put a check in the box next to **Dial-Up Networking**.
8. Click the **OK** button.
9. Click the **OK** button again.
10. Windows 95/98 will prompt you for your installation diskettes or CD.
11. Wait for Dial-Up Networking to install.
12. When you are told to restart, click the **OK** button.
13. Click the **Start** button and choose **Shut Down**.
14. Select **Restart the computer?**
15. Click the **Yes** button.
16. Wait for Windows 95/98 to restart. (This may take a few minutes).

Add a Dial-up Adapter

1. Click the **Start** button point to **Settings** and choose **Control Panel**.
2. Click the **Network** icon.
3. Select the **Configuration** tab.
4. Click the **Add** button.
5. Select **Adapter**.
6. Click the **Add** button.
7. From the **Manufactures:** list, choose **Microsoft**.

8. From the **Network Adapters:** list, choose **Dial-up Adapter**.
9. Click the **OK** button.

Add TCP/IP

1. Click the **Start** button point to **Settings** and choose **Control Panel**.
2. Click the **Network** icon.
3. Select the **Configuration** tab.
4. Click the **Add** button.
5. Select **Protocol**.
6. Click the **Add** button.
7. From the **Manufactures:** list, choose **Microsoft**.
8. From the **Network Protocol:** list, choose **TCP/IP**.
9. Click the **OK** button.

Add Client for Microsoft Networks

1. Click the **Add** button.
2. Select **Client**.
3. Click the **Add** button.
4. From the **Manufacturers:** list, select **Microsoft**.
5. From the **Network Clients:** list, select **Client for Microsoft Networks**.
6. Click the **OK** button.

Create a New Dial-Up Networking Connection

1. Double-click the **My Computer** icon.
2. Double-click the **Dial-Up Networking** folder.
3. Double-click the **Make New Connection** icon.
4. Under **Type a name for the computer you are dialing**, type **DSLnet**
5. Click the **Configure** button.
6. Check that the appropriate speed for your modem (for 14.4 modems use **19200**, for 28.8 modems use **38400** and for 33.6 and 56K modems, use **57600**.)
7. Make sure that **Only connect at this speed** is not checked.

8. Click the **OK** button.
9. Click the **Next** button.
10. In the **Area code** and **Telephone number** text boxes, type your local DSLnet access number. Click the **Next** button.
11. Click the **Finish** button.
12. Click the **DSLnet** icon.
13. From the menu bar, click **File** and select **Properties**.
14. Click the **Server Type** Tab.
15. For **Type of Dial-Up Server**, select **PPP: Windows 95, Windows NT, Internet**.
16. Uncheck **Log on to network**.
17. Check **Enable software compression**.
18. Uncheck **Require encrypted password**.
19. Uncheck **NetBEUI**.
20. Uncheck **IPX/SPX Compatible**.
21. Check **TCP/IP**.
22. Click the **TCP/IP Settings** button.
23. Select the **Server assigned IP address** button.
24. Select the **Server assigned name server addresses**.
25. Check both **Use IP header compression** and **Use default gateway on remote network**.
26. Click the **OK** button.
27. Click the **OK** button.
28. Click the **OK** button.
29. Click the **OK** button to close the window.